


Medium Duty Variable Speed Pan Tilt



ZA-PT540

Model	ZA-PT540
Max. Payload	30kg
Load Mode	Top load
Driving	Worm and gear driving
Pan Rotation Angle	360° continuous
Tilt Rotation Angle	- 45° ~ +40°
Pan Speed	0.01°/s ~ 20°/s
Tilt Speed	0.01°/s ~ 10°/s
Preset Position	200
Presetting Precision	±0.1°
Lens Preset	Support, adaptive to variety of lenses
Lens control speed	Zoom, focus speed is continuously adjustable
Speed Self-adaption	Support
Auto Scan	support
Auto Cruise	support
Keep Watch	Support
Power Failure Memory	Support
Communication Interface	RS485/ RS422 optional
Protocol	Pelco D
Baud Rate	2400/4800/9600/19200 bps optional
Angle query return	RS485, support angle return by query command/ (Optional RS422, support angle real-time return)
System	
Input Voltage	AC24V±25% 50/60HZ ; DC24V±10%
Consumption Power	≤100W
Interface	10/100M Ethernet * 1 ; AC24V /DC24V * 1 ; Optional : RS485 / RS422
Working Temperature	- 35°C ~ + 65°C
Humidity	< 90%RH
Anti-lighting	Power : 4000V (line to ground 4000 V, line to line 2000V) , Video signal : 2000V (line to ground 2000 V, line to line 1000V)
Salt fog resistance	PH 6.5 ~7.2, continuous spraying 48 hours
Waterproof	IP66
Material	Aluminum alloy
Weight	17kg